Shandong Derui Industry & Trade Co., Ltd.
WhatsApp: 86 185 1898 9802
WhatsApp: 852 5587 9103
Email: glenadamson30@gmail.com
WeChat: 86 1851898 9802
Lixia District, Jinan City, Shandong Province

产品目录
PRODUCT CATALOG

山东德瑞工贸有限公司



COMPANY PROFILE

Shandong Derui Co., Ltd. is located in Jinan, Shandong Province. Derui's products cover a wide range of vehicles, including low-speed new energy vehicles, electric passenger tricycles, electric cargo tricycles, leisure tricycles, electric pickups, electric tuk-tuks, and more.

The company has two production bases with a construction cost of $1 billion, covering over 2,000 acres and employing more than 1,500 people. These factories can produce 400,000 new energy vehicles each year and have earned EEC, CCC, and ISO certifications.

In manufacturing, we use the four major automotive processes (stamping, welding, painting, and assembly). At the same time, we focus on technology, design based on customer needs, and continuously upgrade our new products to lead the high-end market.

We are looking for global regional distributors to join Derui and create wealth together.

Building Area	Number Of Workers	Automobile Production Process	Annual Production
2,000 acres	**1,500+**	**4**	**40万+**



A800

EEC / COC / L2e-P

Model	A800	Dimensions(mm)	2400*1245*1619	Body type	integral body
Body structure	2doors and 2seats	Motor	60V1500W AC	Controller	60V 24tubes
Battery(kwh)	60V80AH	Charging time(H)	6-8	Range per charge/km	⩾90
Front suspension	hydraulic shocker	Rear suspension	Drag-arm suspension	Front/rear tire	120/70R12 135/70R12
Rim	Aluminum Alloy Hub	Brake system	front/rear:disc	Climbing degree (%)	⩾25
Top speed(km/h)	45km/h	Steering Mode	Middle Handlebar	Certificate	EEC / COC / L2e-P
Container Capacity	9 PCS SKD/40'HQ				
Function Device	One Button Start	LED lights	Reverse Camera	Heater	Electric window



A801

EEC / COC / L2e-P

Model	A801	Dimensions(mm)	2400*1245*1619	Body type	integral body
Body structure	2doors and 2seats	Motor	60V1500W DC	Controller	60V 24tubes
Battery(kwh)	60V80AH	Charging time(H)	6-8	Range per charge/km	⩾90
Front suspension	hydraulic shocker	Rear suspension	Drag-arm suspension	Front/rear tire	120/70R12 135/70R12
Rim	Aluminum Alloy Hub	Brake system	front/rear:disc	Climbing degree (%)	⩾25
Top speed(km/h)	25km/h	Steering Mode	Middle Handlebar	Certificate	EEC / COC / L2e-P
Container Capacity	9 PCS SKD/40'HQ				
Function Device	One Button Start	LED lights	Reverse Camera	Heater	Electric window



M1

CCC

Model	M1	Dimensions(mm)	2250*1080*1600	Body type	semi-integral body
Body structure	2doors and 2seats	Motor	72V1200W	Controller	72V 24tubes
Battery(kwh)	72V32AH lead acid battery	Charging time(H)	6-8	Range per charge/km	50
Front suspension	Fork suspension	Rear suspension	Drag-arm suspension	Front/rear tire	4.00-10
Rim	Aluminum Alloy Hub	Brake system	front/rear:disc	Climbing degree (%)	⩾25
Top speed(km/h)	45km/h	Steering Mode	Handlebar	Certificate	CCC
Container Capacity	12 PCS CBU/40'HQ				
Function Device	One Button Start	LED lights	Reverse Camera		



N8 PRO

CCC

Model	N8PRO	Dimensions(mm)	2520*1250*1680	Body type	semi-integral body
Body structure	5 doors and 5 seats	Motor	60V1000W	Charging time(H)	6-8
Controller	60V 18tubes	Battery(kwh)	60V58AH	Rear suspension	Drag-arm suspension
Range per charge/km	⩾60	Front suspension	hydraulic shocker	Brake system	front/rear:disc
Front/rear tire	4.00-10 4.00-10	Rim	Aluminum Alloy Hub	Steering Mode	Middle Handlebar
Climbing degree (%)	⩾25	Top speed(km/h)	38km/h	Certificate	CCC
Container Capacity	8PCS SKD/40'HQ	Function Device	LED lights	Reverse Camera	



C6

CCC

Model	C6	Dimensions(mm)	1550*730*1040	Front fork	ϕ27 hydraulic shocker
Motor	60V500W	Controller	60V 12tubes	Front/rear tire	3.0-8 tubeless tire
Rim	Iron Hub	Brake system	front: drum / rear:drum	Charging time(H)	6-8
Range per charge/km	40	Climbing degree (%)	⩾25	Container Capacity	99 PCS SKD/40'HQ
Top speed(km/h)	25km/h	Battery	60V20AH lead acid battery	Certificate	CCC



N5

CCC

Model	N5	Dimensions(mm)	2120*900*1030	Front fork	ϕ27 hydraulic shocker
Motor	60V800W	Controller	60V 15tubes	Front/rear tire	3.0-8 tubeless tire
Rim	Iron Hub	Brake system	front: drum / rear:drum	Charging time(H)	6-8
Range per charge/km	40	Climbing degree (%)	⩾25	Certificate	CCC
Top speed(km/h)	25km/h	Battery	60V20AH lead acid battery	Container Capacity	60PCS SKD/40'HQ



S1

EEC / COC / L2e-P

Model	S1	Overall Dim(mm)	1547*801*1077	Front fork	ϕ27 hydraulic shocker
Motor	60V1000W	Controller	60V 18tubes	Front/rear tire	3.0-10 tubeless tire
Rim	Aluminum Alloy Hub	Brake system	front: disc / rear:drum	Charging time(H)	6-8
Range per charge/km	40	Climbing degree (%)	⩾25	Certificate	EEC / COC / L2e-P
Battery	60V20AH lead acid battery	Top speed(km/h)	25km/h	Container Capacity	99 PCS SKD/40'HQ



P100

EEC / COC / L2e-P

Model	P100	Overall Dim(mm)	2285*975*1048	Front fork	ϕ31 hydraulic shocker
Motor	60V1000W	Controller	60V 18tubes	Front/rear tire	3.0-10 tubeless tire
Rim	Aluminum Alloy Hub	Brake system	front: disc / rear:drum	Charging time(H)	6-8
Range per charge/km	40	Climbing degree (%)	⩾25	Certificate	EEC / COC / L2e-P
Battery	60V20AH lead acid battery	Top speed(km/h)	25km/h	Container Capacity	48 PCS SKD/40'HQ



PM7

CCC

Model	PM7	Dimensions(mm)	2140*1100*1725	Front fork	ϕ27 hydraulic shocker
Motor	60V800W	Controller	60V 15tubes	Front/rear tire	3.0-8 tubeless tire
Rim	Iron Hub	Brake system	front: drum / rear:drum	Charging time(H)	6-8
Range per charge/km	40-60	Climbing degree (%)	⩾25		
Top speed(km/h)	25km/h	Battery	60V32AH lead acid battery		
Container Capacity	22 PCS SKD/40'HQ	Certificate	CCC		



A900

EEC / COC / L7e-CP

Model	A900	Dimensions(mm)	2810*1316*1509	Body type	integral body
Body structure	4doors and 4seats	Motor	72V3000W AC	Controller	72V 24tubes
Battery(kwh)	72V100AH	Charging time(H)	6-8	Range per charge/km	⩾90
Front suspension	McPherson suspension	Rear suspension	Drag-arm suspension	Front/rear tire	135/70R12
Rim	Aluminum Alloy Hub	Brake system	front/rear:disc	Climbing degree (%)	⩾25
Top speed(km/h)	45km/h	Steering Mode	Steering	Certificate	EEC / COC / L7e-CP
Container Capacity	5 PCS SKD/40'HQ	LED lights	Reverse Camera	Heater	Electric window
Function Device	One Button Start				



A8P

EEC / COC / L6e-BP

Model	A8P	Dimensions(mm)	2545*1227*1610	Body type	integral body
Body structure	2doors and 2seats	Motor	60V3000W AC	Controller	60V 24tubes
Battery(kwh)	60V80AH	Charging time(H)	6-8	Range per charge/km	⩾90
Front suspension	McPherson suspension	Rear suspension	Drag-arm suspension	Front/rear tire	135/70R12
Rim	Aluminum Alloy Hub	Brake system	front/rear:disc	Climbing degree (%)	⩾25
Top speed(km/h)	45km/h	Steering Mode	Steering	Certificate	EEC / COC / L6e-BP
Container Capacity	9 PCS SKD/40'HQ	Function Device	One Button Start	LED lights Reverse Camera/ Heater/ Electric window	



A901

EEC / COC / L7e-CP

Model	A901	Dimensions(mm)	2810*1316*1509	Body type	integral body
Body structure	4doors and 4seats	Motor	72V3000W AC	Controller	72V 24tubes
Battery(kwh)	72V100AH	Charging time(H)	6-8	Range per charge/km	⩾90
Front suspension	McPherson suspension	Rear suspension	Drag-arm suspension	Front/rear tire	135/70R12
Rim	Aluminum Alloy Hub	Brake system	front/rear:disc	Climbing degree (%)	⩾25
Top speed(km/h)	45km/h	Steering Mode	Steering	Certificate	EEC / COC / L7e-CP
Container Capacity	5PCS SKD/40'HQ				
Function Device	One Button Start	LED lights	Reverse Camera	Heater	Electric window



M1P

EEC / COC / L6e-BP

Model	M1P	Dimensions(mm)	2450*1320*1620	Body type	semi-integral body
Body structure	2doors and 2seats	Motor	72V2000W	Controller	72V 24tubes
Battery(kwh)	72V45AH lead acid battery	Charging time(H)	6-8	Range per charge/km	50
Front suspension	Integrated suspension	Rear suspension	Drag-arm suspension	Front/rear tire	125/60R12
Rim	Aluminum Alloy Hub	Brake system	front/rear:disc	Climbing degree (%)	⩾25
Top speed(km/h)	45km/h	Steering Mode	Steering	Certificate	EEC/COC/L6e-BP
Container Capacity	8 PCS CBU/40'HQ	Function Device	LED lights	Reverse Camera	One Button Start



T5P

EEC

Model	T5P	Dimensions(mm)	2757*1292*1647	Body type	semi-integral body
Body structure	4doors and 4seats	Motor	72V5000W	Controller	72V 32tubes
Battery(kwh)	72V58AH lead acid battery	Charging time(H)	6-8	Range per charge/km	⩾60
Front suspension	Integrated suspension	Rear suspension	Drag-arm suspension	Front/rear tire	125/65-12
Top speed(km/h)	50km/h	Steering Mode	Steering	Container Capacity	5 PCS SKD/40'HQ
Rim	Aluminum Alloy Hub	Brake system	front/rear:disc	Climbing degree (%)	⩾25
Certificate	EEC	Function Device	One Button Start	LED lights	Reverse Camera



V300

CCC

Model	V300	Dimensions(mm)	3100*1510*1550	Body type	semi-integral body
Body structure	4doors and 4seats	Motor	60V3000W AC	Controller	60V 24tubes
Battery(kwh)	60V100AH	Charging time(H)	6-8	Range per charge/km	⩾80
Front suspension	Integrated bridge suspension	Rear suspension	Drag-arm suspension	Front/rear tire	145/70R12
Rim	Aluminum Alloy Hub	Brake system	front/rear:disc	Climbing degree (%)	⩾25
Top speed(km/h)	45km/h	Steering Mode	Steering	Container Capacity	4 PCS SKD/40'HQ
Certificate	CCC				
Function Device	One Button Start	LED lights	Reverse Camera	Heater	Electric window



P3K

CCC

Model	P3K	Dimensions(mm)	2770*1180*1615	Body type	semi-integral body
Body structure	2doors and 2seats	Motor	60V1000W	Controller	60V24tubes
Battery	60V45Ah	Charging time(H)	6-8	Range per charge/km	50km
Loading capacity/kg	400kg	Front suspension	ϕ37 hydraulic fork	Rear suspension	Integrated rear axle
Front/rear tire	4.0-10/4.0-10	Rim	Aluminum Alloy Hub	Brake system	front: disc / rear:drum
Climbing degree (%)	⩾20	Top speed(km/h)	30km/h	Steering Mode	handlebar
Certificate	CCC	Container Capacity	10 PCS SKD/40'HQ	Function Device	LED lights Reverse Camera



A8H

EEC / COC / L7e-CU

Model	A8H	Dimensions(mm)	3559*1227*1669	Body type	semi-integral body
Body structure	2doors and 1seat	Motor	72V5000W	Controller	72V 32tubes
Battery(kwh)	72V120AH	Charging time(H)	6-8	Range per charge/km	⩾90
Loading capacity/kg	1183kg	Front suspension	McPherson suspension	Climbing degree (%)	⩾25
Rear suspension	Integrated rear axle	Front/rear tire	135/70R12	Rim	Iron Hub
Top speed(km/h)	52km/h	Steering Mode	Steering	Brake system	front/rear:disc
Certificate	EEC / COC / L7e-CU	Container Capacity	4 PCS SKD/40'HQ		
Function Device	One Button Start	LED lights	Reverse Camera	Heater	Electric window



LK7

EEC / COC / L7e-CU

Model	LK7	Dimensions(mm)	3500*1330*1720	Cargo box size(mm)	1800*1300*550
Body type	semi-integral body	Body structure	2doors and 2seats	Motor	72V4000W
Controller	72V 32tubes	Battery(kwh)	72V100AH lead acid battery	Charging time(H)	6-8
Range per charge/km	100	Front suspension	Integrated front axle	Rear suspension	Integrated rear axle
Front/rear tire	155/70R12	Rim	iron	Brake system	front/rear:drum
Climbing degree (%)	⩾25	Top speed(km/h)	55km/h	Steering Mode	Steering
Container Capacity	5 PCS SKD/40'HQ	Certificate	EEC / COC / L7e-CU		
Function Device	One Button Start	LED lights	Reverse Camera		



M11

EEC / COC / L2e-U

Model	M11	Overall Dim(mm)	2450*860*1254	Cargo box size(mm)	1028*615
Front fork	ϕ31 hydraulic	Motor	60V1000W	Controller	60V 18tubes
Loading capacity/kg	357kg	Front/rear tire	3.00-12 tire	Rim	iron rim
Brake system	front / rear:drum	Charging time(H)	6-8	Range per charge/km	40-45
Climbing degree (%)	⩾25	Battery	60V32AH lead acid battery	Container Capacity	48PCS SKD/40'HQ
Top speed(km/h)	25km/h	Certificate	EEC / COC / L2e-U		



TW

CCC

Model	TW	Overall Dim(mm)	2940*1130*1310	Cargo box size(mm)	1500*1130*550
Front fork	ϕ37 hydraulic with spring	Motor	60V1000W	Controller	60V 24tubes
Loading capacity/kg	500kg	Front/rear tire	3.75-12 tire	Rim	iron rim
Brake system	front / rear:drum	Charging time(H)	6-8	Range per charge/km	40-60
Climbing degree (%)	⩾25	Battery	60V45AH lead acid battery	Container Capacity	36PCS SKD/40'HQ
Top speed(km/h)	35km/h	Certificate	CCC		



ZS

EEC / COC / L2e-U

Model	ZS	Overall Dim(mm)	3065*1175*1395	Cargo box size(mm)	1600*1175*550
Front fork	ϕ43 hydraulic with spring	Motor	72V1500W	Controller	72V 24tubes
Loading capacity/kg	585kg	Front/rear tire	4.00-12 tire	Rim	iron rim
Brake system	front: disc / rear:drum	Charging time(H)	6-8	Range per charge/km	60-80
Climbing degree (%)	⩾25	Battery	72V58AH lead acid battery	Container Capacity	36PCS SKD/40'HQ
Top speed(km/h)	45km/h	Certificate	EEC / COC / L2e-U		



E5

Model	E5	Dimensions(mm)	2800*1250*1780	CurbWeight(withoutbattery/kg)	310kg
Passenger	1 driver +5 passenger	Motor	72V3000W	Controller	72V 24tubes
Top speed(km/h)	55km/h	Front absorber	hydraulic absorber	Rear absorber	semi-independent suspension
Brake	front: disc / rear:drum	Tyre	Front 3.75-12 rear 4.00-12	Meter	LCD meter
Range per charge/km	90	Climbing degree (%)	⩾25	Battery	72V100AH lead acid battery
Rear video	yes	USB charger	yes	Alarm	yes
Rain Curtain	yes	Container Capacity	27PCS SKD/40'HQ		